

I VZJET



MX690

Continuous Inkjet Printer

**2000 CHARACTERS
HIGH SPEED PRINTING**

APPLICATION



Plastic



Cable



Metal



Carton

PARAMETERS

Language: Chinese、English	Chassis size:550mmx380mmX265mm	Nozzle material: ruby
Printing distance: 2~20mm from the surface of the product	Ambient humidity: range 10~90%(non-condensing)	Nozzle aperture:55 microns 60 microns
Printed lines : 1~4 lines (8x8 dot matrix)	Text input: Full spell input	Nozzle catheter: 2 meters,3 meters,4 meters (standard 2.5 meters)
Printing speed: 2000 characters/sec(5x5)	Working voltage: 110V~240V, 50/60Hz	Nozzle cleaning: independent automatic cleaning
Printing height: adjustable from 1~15mm	Box material: SS 304	Ink type: butanone / alcohol based / mixed base
Printed font: simplified song, simplified black body	Gross Power: 150W	Ink color: Black、Yellow、Red
Printing dot matrix: numbers and letters 8x8 8x16 12x12 16x16 24x24	Weight: NW 35KG	Information Storage: 100 Complex Printed Information
External interface: Photoelectric synchronizer	Protection level: IP55	Inkjet Font:Simplified Characters、Letter、Symbol
Chinese font:12x12 16x16 24x24 Jane Song,Jane Black,and 32 dot matrix custom graphics		Viscosity detection: negative pressure viscosity detection
Optional accessories:Tri-color alarm light ,Color-coded sensor ,Fiber optic sensor		Operating temperature: range 5~45℃

Jr Los Canarios N° 122 Urb. Santa Anita Lima 043 - Perú
Central: **480-0102** Celular: **947 647 287 | 998 430 058**
ventas@sercodin.com | www.sercodin.com

 @sercodin.sac  @sercodiin